50 L KONİK KARIŞTIRMA TANKI

50 L CONICAL MIXING TANK



ÜRÜN TEKNİK ÖZELLİKLERİ

Elektrik motoru: 1 HP, 1400 dev/dak, 220 v, 3p, 50 Hz
Karıştırıcı hızı 0-1400 dev/dak arasında hız kontrol cihazı ile kademesiz ayarlanabilir.

AISI 304 paslanmaz çelik malzemeden imal gövde ve mekanik karıştırma mili ve pervanesi.

Kilitlenebilir tekerlekli çelik konstrüksiyon taşıyıcı şase üzerinde monteli

TECHNICAL DETAILS

Electrical Motor: 1 HP, 1400 rpm, 220 v, 3p, 50 hz provided with an electronic motor speed contoller for infinitely variable speed between 0 - 1400 rpm.

50 lt capacity conical bottomed tank with a mechanical propeller and stirring shaft made of AISI 304 stainless steel

It is mounted on a steel frame with 4 wheels for mobile use.

300 L KONİK KARIŞTIRMA TANKI

300 L CONICAL BOTTOM MIXING TANK



ÜRÜN TEKNİK ÖZELLİKLERİ

Elektrik motoru: 1 HP, 1400 dev/dak, 220 v, 3p, 50 Hz

Özel rulman yatağı ve açılı karıştırma mili ile daha efektif bir karışım sağlar. 0 - 1400 dev/dak arası kademesiz ayarlanabilir karıştırma devri.

Tamamen AISI 304 paslanmaz çelik malzemeden imal.

Ayaklar üzerine monteli.

TECHNICAL DETAILS

Electrical Motor: 1 HP, 1400 rpm, 220 v, 3p ,50 Hz provided with an electronic motor speed contoller for infinitely variable speed between 0 - 1400 rpm.

300 lt capacity conical bottomed tank with a mechanical propeller and stirring shaft made of AISI 304 stainless steel; driven by an

It is mounted on a steel frame for easy use.