BÖHME YÜZEY AŞINDIRMA CİHAZI

BÖHME ABRASION TESTER



ÜRÜN TEKNİK ÖZELLİKLERİ

Elektrik Motoru: 1 HP, 900 dev/dak, 380 v, 3 p, 50 Hz
redüktör tahrikli,TS 699 / MART 2009 a uygun

Ø 750 mm çapında, 30 ± 1 dev/dak dönme hızlı, aşınmaya mukavim döküm diskli
30 kgf ± 0,3 kgf baskı kuvveti uygulayabilen özel manivela kuvvet kolu ve ağırlığı
Çift elektronik dijital devir sayıcılı
1.ci. sayıcı 22 devirde bir cihazı otomatik durdurur
2.sayıcı 20 adet 22 devirlik aşındırma periyodu sonunda (toplam 440 devir) cihazı otomatik durdurur

TECHNICAL DETAILS

Electrical Motor: 1 HP, 900 rpm, 380 v, 3 p, 50 Hz and gear box.
In accordance with TS 699 / MARCH 2009.

Ø 750 mm diameter, 30 ± 1 rpm rotational speed, abrasion resistant cast disc,
A compressive force of 30 ± 0.3 kgf applied on the sample by a special lever arm.
Two electronic digital rev counters
first counter stops the disc automatically after 22 revolutions.
Second counter stops automatically at the end of the 20 periods, containing 22 revolutions, (total working 440 revs.)