JAMESON TİPİ KOLON FLOTASYON CİHAZI

COLUMN FLOTATION (JAMESON TYPE)





ÜRÜN TEKNİK ÖZELLİKLERİ

Şeffaf Dairesel kesitli Kolon Hücresi Çapı : 200 mm
Kolon Yüksekliği : 900 mm
Pülp Beslemesi için devir ayarlı peristaltik pompalı,50 lt hacminde, tabanı konik, paslanmaz çelik, hızı ayarlanabilir, mekanik karıştırmalı Pülp Besleme Tankı, 50 lt hacminde, tabanı konik, paslanmaz çelik Yıkama Suyu Besleme Tankı ile tekmil. Su ,hava debisi ölçme ve kontrol debimetreleri ile tekmil.Konsantre yıkamak için mikronize atomizer su püskürtme nozılları ile tekmil.Komple sistem kilitlenebilir tekerlekli seyyar kullanılabilir bir çelik sehpa üzerinde kurulu olarak. 1000 x 2100 x 3600 mm dış ölçüleri (E X B X Y)

TECHNICAL DETAILS

One column is made of transparent acrylic colorless circular pipe. Cell Column Diameter: 200 mm and Height: 900 mm.Provided with a peristaltic pump with infinirely variable speed adjustment for precise pulp feeding.A conical bottomed 50 liters capacity pulp supply tank, with infinitely variable speed controlled stirring electrical motor, and a a conical bottomed 50 liter capacity,washing water supply tank, all are made of AISI 304 stainless steel. Provided with water and air flow control and measuring flowmeters.Provided with a pressurized concentrate wash water system with a centrifugal water pump , water reservoir with float valve, pressure gauge, by pass valve and spray nozzles. Concentrate Washing water ejected from the nozzle can be easily adjusted between 10 - 100 liter/hour by a flowmeter.All the system is mounted on a steel frame with 4 wheels for mobile use. 1000 x 2100 x 3600 mm outside dimensions (W X L X H)